

# Großes und elegantes professionelles 4K Signage- Display

TH-75SQ1

Ausgerüstet mit fortschrittlichen professionellen Funktionen bietet es eine schlanke, leichte und skalierbare Lösung, die jegliche Installationen erleichtert. 4K Ultra HD-Panel mit 75", Intel® Smart Display Module (Intel® SDM), Dauerbetrieb, Hochformat, 4K Digital Link, schmaler Rahmen



## KEY FEATURES

- 4K IPS-Panel mit 75" und 500 cd/m2 mit schlankem und elegantem Design für Dauerbetrieb
- Hohe Bildqualität durch HDR-Unterstützung (HLG-System), sodass helle und dunkle Bilder auf realistische Weise angezeigt werden
- 4K-USB-Media-Player: externe Geräte werden überflüssig und Updates über LAN ermöglicht
- Umfassende Erweiterbarkeit mit extrem schmalen Intel® SDM (Intel® Smart Display Module), DisplayPort-Anschluss für Daisy-Chain-Signage, Unterstützung von mehreren Bildschirmen (Quad, PinP, PbyP) und 4K DIGITAL LINK
- Flexible und leichte Installation entweder im Hoch- oder Querformat

Großes, professionelles und elegantes 4K-Signage-Display. Ausgerüstet mit fortschrittlichen und professionellen Funktionen bietet es eine schlanke, leichte und skalierbare Lösung, die jegliche Installationen erleichtert.

500 cd/m<sup>2</sup>

## SPECIFICATIONS

Screen size (diagonal) (inch)	74.5 inch
Screen size (diagonal) (mm)	1892.7 mm
Aspect Ratio	16:9
Panel Type	IPS / Edge LED
Effective display area (W x H) (mm)	1649.6 mm / 927.9 mm
Effective display area (W x H) (inch)	64.94" / 36.53"
Auflösung	3840 x 2160
Brightness (typ.)	500 cd/m <sup>2</sup>
Contrast Ratio	1200:1
Response Time	8.0 ms (G to G)
Viewing angle [(T/B)/(L/R)]	178° / 178° (CR <sub>≥</sub> 10)
Power Requirements	AC 110 - 240 V 50 Hz / 60 Hz
Terminals   HDMI In	HDMI Type A Connector x 2(Compatible with HDCP 2.2)AUDIO: Linear PCM (Sampling frequency)48 kHz/44.1 kHz/32 kHz)
Terminals   DVI-D IN/AUDIO IN (L/R)	DVI-D 24-pin x 1 (Compatible with HDCP 1.1) Compliance with DVI Revision 1.0
Terminals   PC IN/AUDIO IN (L/R)	Mini D-Sub 15-pin (DDC2B) x 1 Y/GPB/CB/BPR/CR/RHD/VD: with sync 1.0 V [p-p] (75 Ω): without sync 0.7 V [p-p] (75 Ω): without sync 0.7 V [p-p] (75 Ω): without sync 0.7 V [p-p] (75 Ω): HD/VD TTL (high impedance)
Terminals   DisplayPort IN	Display Port x 1(Compatible with HDCP 2.2)AUDIO: Linear PCM (Sampling frequency)48 kHz/44.1 kHz/32 kHz)
Terminals   DisplayPort OUT	Display Port x 1 (Compatible with HDCP 1.4)
Terminals   USB	USB Connector (Type A) x 2, DC 5 V/2A, DC 5 V/1A (USB 3.0 is supported)
Terminals   Serial	D-sub 9-pin x 1, RS-232C Compatible
Terminal   LAN	RJ45 x 1 compatible with PLinkTMRJ45 10BASE10-T/100BASE-TX
Terminal   DIGITAL LINK	RJ45 x 1 100BASE-TX, compatible with Long reach mode (Compatible with HDCP 2.2)
Terminals   Slot	Intel® SDM specificationCorresponding size SDM-S / SDM-L, Supply power 3.3 V / 1.1 A, 12 V / 5.5 A
Terminals   IR IN / OUT	Stereo Mini Jack (M3) x 1 / x 1
Terminals   Audio Out	Stereo Mini Jack (M3) x 1 0.5 V [rms]Variable (-∞ - 0 dB) (1 kHz 0 dB Input, 10 kΩ Load)
Built-in Speaker	20 W [10 W + 10 W]
Power Consumption	385 W
Power Off Condition	approx. 0.3 W
Stand-by Condition	approx. 0.5 W
Dimensions (W x H x D) (mm)	1681 mm x 959 mm x 73 mm
Dimensions (W x H x D) (inch)	W 66.15" x H 37.75" x D 2.87"
Carton Size (W x H x D) (mm)	1832 x 1283 x 280 mm
Carton Size (W x H x D) (inch)	72.2 x 50.6 x 11.1"
Bezel width (mm)	T/B/L/R: 14.8 mm
Bezel width (inch)	T/B/L/R: 0.58"

<b>Weight (kg)</b>	approx. 56.0 kg
<b>Weight (lbs.)</b>	123.5 lbs
<b>Gross Weight (kg)</b>	71 kg
<b>Gross Weight (lbs.)</b>	156.6 lbs
<b>Wall-hanging pitch (mm)</b>	VESA Compliant W 600 x H 400 mm (Installed by: M6 screws / Screw hole depth 10 mm)
<b>Tilting angle</b>	Landscape : 0 - 45 degrees forward / backward Portrait : 0 - 20 degrees forward / backward
<b>Operating Time</b>	24h / day
<b>Operating environment   Temperature</b>	0 °C to 40 °C (32 °F to 104 °F)*1 : 0 °C to 35 °C (32 °F to 95 °F)* *: for between 1400 m (4593 ft) and 2800 m (9186 ft) altitude
<b>Operating Environment   Humidity</b>	20% to 80% (No condensation)
<b>Dynamic Contrast ratio</b>	50000:1
<b>Panel Surface Treatment</b>	Anti glare type (Haze 28%)

URL: <https://business.panasonic.de/visuelle-systeme/th-75sq1>

## CONTACT

Web: <https://business.panasonic.de/visuelle-systeme/contact-us>