

Heller, kompakter und einfach zu bedienender Projektor mit niedrigen Gesamtbetriebskosten

PT-LW376

Konzipiert für den Einsatz im Bildungswesen und in Unternehmensumgebungen. LCD-Projektor mit 3.600 Lumen und WXGA.



KEY FEATURES

- LCD, 3.600 Lumen, WXGA
- Lampen- und Filterwechselzyklus von bis zu 10.000 Stunden (niedrigere Gesamtbetriebskosten)
- Leises Betriebsgeräusch von nur 28 dB für Projektionen ohne Ablenkung
- Kabellose Projektion (optional)
- Kontrastverhältnis von 16.000:1

SPECIFICATIONS

Dimensions (W x H x D)	335 x 96*3 x 252 mm (13 3/16" x 3 25/32" *3 x 9 29/32")
Power Consumption	300 W
Lens	Manual zoom (1.2x), manual focus lens, F = 1.6–1.76, f = 19.16–23.02 mm, throw ratio: 1.48–1.78:1
Auflösung	1280 x 800 pixels
Operating Environment	Operating temperature: 5–40 °C (41–104 °F), operating humidity: 20–80 % (no condensation)
Keystone Correction Range	Vertical: ±35 ° (Auto, Manual), Horizontal: ±35 ° (Manual) (TBD)
Installation	Ceiling/floor, front/rear
Cabinet Materials	Molded plastic
Applicable Software	Multi Monitoring & Control Software, Presenter Light Software (for Windows®), Wireless Projector
Contrast Ratio*1	20,000:1 (All white/all black, Iris: On, Image mode: Dynamic, Lamp control: Normal)
Power Supply	AC 100–240 V, 50/60 Hz
Light Source	230 W x 1 lamp
Terminals LAN	RJ-45 x 1 for network connection, 10Base-T/100Base-TX, PLink™ (Class 1) compatible
Terminals HDMI In	HDMI 19-pin x 2 (Compatible with HDCP 1.4, Deep Color), Audio signal: Linear PCM (Sampling frequencies: 48 kHz, 44.1 kHz, 32 kHz)
Light output	3,600 lm
Operation noise*1	Normal: 38 dB, Eco: 35 dB, Quiet: 30 dB
Screen size [diagonal]	0.76–7.62 m (30–300 in), 16:10 aspect ratio
Center-to-corner zone ratio*1	85 %
Time until light output declines to 50 %*3	20,000 hours (NORMAL)
Note	*1 Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards. *2 Lamp replacement cycle stated is maximum value, at which time brightness will have decreased to 50 %. Usage environment affects lamp replacement cycle. *3 With legs at shortest position. *4 Average value. May differ depending on the actual unit.
Terminals Computer 1 In	D-sub HD 15-pin (female) x 1 [RGB/S-Video/YPB(CB)PR(CR)]
Terminals Video In	Pin jack x 1
Terminals Audio In 1	M3 (L,R) x 1
Terminals Serial In	D-sub 9-pin (female) x 1 for external control (RS-232C compatible)
Terminals Audio Out	M3 (L,R) x 1 (Variable)
Terminals Computer 2 In/1 Out	D-sub HD 15-pin (female) x 1 [RGB]
LCD Panel Panel Size	15.0 mm (0.59 in) diagonal (16:10 aspect ratio)
LCD Panel Display Method	Transparent LCD panel (x 3, R/G/B)
LCD Panel Drive Method	Active matrix method
LCD Panel Number of pixels	1,024,000 (1280 x 800 pixels) x 3
Built in Speaker	10 W monaural
Terminals Audio In 2	Pin jack x 2 (L,R)
Filter Replacement Cycle	Normal: 5,000 h/Eco: 6,000 h/Quiet: 10,000 h
Weight*4	Approx. 2.9 kg (6.4 lbs)
Lamp replacement cycle*2	Normal: 10,000 h/Eco: 20,000 h/Quiet: 10,000 h
Terminals USB B	-
Terminals USB A	USB Type-A (for Memory Viewer Light/Wireless Module [Output 5 V/2 A])

URL: <https://business.panasonic.de/visuelle-systeme/Tragbarer-Projektor/PT-LW376>

CONTACT

Web: <https://business.panasonic.de/visuelle-systeme/contact-us>