

Weltweit schlankstes Videowall-Display mit Randabstand von 0,88 mm

TH-55VF2H

Ideale Lösung für große, fesselnde Videowalls mit extrem schmalen Rahmen und den Einsatz in den Bereichen Digital Signage, Broadcast und Leitstellen.



KEY FEATURES

- Rahmenloses D-LED LCD-Display (55 Zoll), 500 cd/m², Randabstand 0,88 mm, 24/7-Dauerbetrieb, IPS-Panel mit blendfreier Oberfläche (Dunst 28 %).
- Modernste Gleichmäßigkeit für einheitlich hohe Bildqualität.
- Widerstandsfähige Failover- und Failback-Funktion mit vereinfachtem Workflow
- Unterstützt Reverse-Scan und Frame-Steuerung für verbesserte Multi-Screen-Video-Sichtbarkeit
- Supports reverse scan and frame control to improve multi-screen video visibility

Unübertroffen nahtlose Videowalls



SPECIFICATIONS

Screen Size	54.6-inch(1387.8 mm)
Panel Type	IPS/D-LED
Aspect Ratio	16:9
Effective Display Area (W x H)	1209.6 x 680.3 mm(47.62" x 26.78")
Number of Pixels (H x V)	1920 x 1080 pixels
Helligkeit	500 cd/m ²
Contrast Ratio	1100:1
Response Time	8.0 ms(G to G)
Viewing Angle	178° / 178° (CR ≥ 10)
Panel Surface Treatment	Advanced Anti-glare type (Haze 28%)
Haze	28%
Terminals HDMI In	Type A Connector x 1
Terminals DisplayPort IN	DisplayPort DP1.1 Dual Mode Only) x 1
Terminals DVI-D IN/AUDIO IN (L/R)	DVI-D 24-pin x2
Terminals PC IN/AUDIO IN (L/R)	Mini D-sub 15-pin x 1 (Female)
Terminals Serial In/Out	D-sub 9pin x 1 / x 1, RS-232C Compatible
Terminals IR In/Out	Stereo Mini Jack (M3) x 1 / x 1
Terminals Audio Out	Stereo Mini Jack (M3) x 1 Variable (-∞ - 0 dB) (1 kHz 0 dB Input, 10 k Ω Load)
Terminals LAN	RJ45 x 1 / x 1, 100 BASE-TX, Compatible with PLink™ (Shared with DIGITAL LINK)
Terminals USB	USB 2.0 Type A connector x 1 DC 5 V / 500 mA (USB3.0 is not supported.)
Dimensions (W x H x D)	1210.6 x 681.3 x 97.3 mm / 47.658" x 26.820" x 3.829"
Gewicht	approx. 23.0 kg / approx. 50.7 lbs
Bezel Width	T / B / R / L 0.44 mm / 0.018"
Wall-Hanging Pitch	VESA Compliant 400 x 400 mm / 15.8" x 15.8" (Installed by: M6 screws / Screw hole depth 12 mm / 0.47")
Operating Time	24 h/day
Operating Environment	Temperature: 0 °C to 40 °C (32 °F to 104 °F)/Humidity: 20-80 % (Non condensation) /for up to 0-1400 m (4593 ft) altitude. Temperature: 0 °C to 35 °C (32 °F to 95 °F)/Altitude 1400 -2800 m (4593 ft to 7874 ft)
Power Requirements	AC 110 - 127 V 50Hz/60Hz AC 220 - 240 V, 50 Hz/60 Hz
Power Off Condition	approx. 0 W
Standby Condition	approx. 0.5 W
Power Consumption	300 W
Speaker	2Ω, 20 W [10 W] 10 % THD
Carton Dimensions (W x H x D)	1395 x 848 x 280 mm / 55.0" x 33.4" 11.1"
Gross Weight	34 kg / 75.0 lbs
On Mode Average Power Consumption*	165 W *Based on IEC 62087 Ed.2 measurement method

URL: <https://business.panasonic.de/visuelle-systeme/th-55vf2h>

CONTACT

Web: <https://business.panasonic.de/visuelle-systeme/contact-us>