Product Family

SKU technical specifications



	SRTL1000RMXLI SRTL1000RMXLI-NC*	SRTL1500RMXLI SRTL1500RMXLI-NC*	
Topology	Double Conversion On-Line		
Output			
Output Power Capacity	900 Watts / 1000 VA	1350 Watts / 1500 VA	
Nominal Output Voltage	23	0V	
Output Voltage Distortion	Less than 2% at full load		
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz (auto sensing)		
Waveform Type	Sine wave		
Output Connections	(8) IEC3		
Switched outlet Groups	(o) 1200 Ye		
Efficiency at Full Load	>91%	>92%	
Input	2 0 1 70	- 02/0	
Nominal Input Voltage	230	n\/	
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)		
Input Connections	IEC320 C14		
·	160-275V		
Input voltage range for main operations Batteries & Runtime			
Battery Type	Lithiu	m-lon	
Standard Runtime at full load	32min at 900W	19min at 1350W	
Replacement Battery	XBP48RM1U-LI	(external Li-lon battery pack)	
Communications & Management	7.5. 10.1 2.	(onto man in to matter) passey	
Interface Port(s)	Serial (RJ45), S	Smart-Slot USB	
	1		
Available SmartSlot™ Interface Quantity			
Control panel	Multi-function LCD status and control console		
Audible Alarm	Audible and visible alarms prioritized by severity		
Emergency Power Off (EPO)	Yes		
*Preinstalled Network Management Card	included with "NC" suffix SKU		
Physical			
UPS			
Net HxWxD	85mm x 432mm x 587mm	85mm x 432mm x 587mm	
Rack Height	2U	2U	
Net Weight	13.7kg	13.7kg	
Shipping Weight -	21kg	21kg	
Shipping HxWxD	445mm x 600mm x 850mm	445mm x 600mm x 850mm	
Color	Black	Black	
Lithium Ion External Battery Pack			
Net HxWxD	85mm x 432mm x 510mm		
Rack Height	1U		
Net Weight	12kg		
Shipping Weight -	16.4kg		
Shipping HxWxD	200mm x 600mm x 850mm		
Environmental			
Operating Environment	32 - 104 °F (0 - 40 °C)		
Operating Relative Humidity	0 - 95%		
,	0-10000 feet (0-3000 meters)		
Storage Temperature	-15 to 45 °C (-30 to 70°C without batteries)		
Storage Relative Humidity	0 - 95%		
Storage Elevation	0-50000 feet (0-15000 meters		
	50.0dBA		
Online Thermal Dissipation	400 BTU/hr		
Conformance	-	-	
	VDE, EAC, CE, RCM, EN/IEC 62040-1		
, , , , , , , , , , , , , , , , , , ,	5 years on UPS and		
Standard Warranty	5 years on battery pack		
		repair or replace	
Operating Relative Humidity Operating Elevation Storage Temperature Storage Relative Humidity Storage Elevation Audible noise at 1 meter from surface of unit Online Thermal Dissipation Conformance Regulatory Approvals	0 - 95% 0-10000 feet (0-3000 meters) -15 to 45 °C (-30 to 70°C without batteries) 0 - 95% 0-50000 feet (0-15000 meters 50.0dBA 400 BTU/hr VDE, EAC, CE, RCM, EN/IEC 62040-1 5 years on UPS and 5 years on battery pack		

